





SM2011-R35MHF



Features:

- 5.7x5.4mm foot print, 3mm height SMD molded inductor.
- High saturation current characteristics by distributed gapped metal dust core.
- Ideally for portable device, notebook, server computer and high density DC to DC converter applications
- T & R Quantity: 1,000 piece per reel.
- RoHS Compliance and Halogen Free
- Operating Temperature Range -55°C to +125°C



Suggested Pad Layout:
(in mm):

Series	SM2011
A	2.79
B	2.16
C	5.99

Mechanical Dimmensions (Unit: mm)					
ITG Part Number	A ± 0.25	B ± 0.25	C Max.	D ± 0.30	E ± 0.30
SM2011-R35MHF	5.49	5.18	3.00	2.00	1.02

Electrical Specifications:					
Part Number	L ± 20% @0A (μH)	R _{DC} Typical (mohm)	R _{DC} Max. (mohm)	I _{rms} (A)	I _{sat} (A)
SM2011-R35MHF	0.35	3.90	4.29	16.60	14.90

Notes:

1. DC current (I_{rms}) that will cause an approximate temperature rise ΔT of 40°C
2. DC current (I_{sat}) that will cause L_o to drop approximately 30%
3. All inductance and I_{sat} is measured at 100Khz 0.25V, 25°C ambient
4. Operating Temperature Range -55°C to +125°C
5. The part temperature (ambient + temp rise) should not exceed 125°C under worst case operating conditions. Circuit design, component placement, PWB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.

Inductance vs. Current vs. Temperature Rise

