



SM2518A Series



1. Features of SM2518A series:


- 7.30 x 6.80mm Foot Print , 5.00mm Max. height SMD Power Inductor for high frequency application. Operating frequency up to 5MHz.
- Inductance range from 0.22uH to 6.80 uH. Custom values are welcomed.
- High saturation current characteristics by distributed gapped metal dust core.
- Ideal for portable device, Pad, E-reader and high density DC to DC Converter
- Operating Temperature Range: -55°C to 155°C .
- Tape & Reel Quantity: 1000 piece per 13 inches reel. RoHS and HF compliant.



2. Electrical Characteristics of SM2518A series:

ITG Part Number	Inductance ¹ (uH) ± 20%	DCR (mΩ) Typ. @25°C	DCR (mΩ) Max. @25°C	Saturation Current ² Isat (A) Typ @25°C	Heat Rating Current ³ Irms (A) Typ. @25°C
SM2518A-R22MHF	0.22	1.10	1.30	32.00	30.00
SM2518A-R36MHF	0.36	2.70	3.10	25.00	21.00
SM2518A-R47MHF	0.47	3.30	3.75	22.00	20.00
SM2518A-R68MHF	0.68	3.80	4.20	17.00	18.00
SM2518A-1R0MHF	1.00	5.60	6.50	15.00	13.00
SM2518A-1R5MHF	1.50	6.00	7.50	12.00	11.00
SM2518A-2R2MHF	2.20	11.20	12.50	11.00	10.50
SM2518A-3R3MHF	3.30	19.90	20.90	9.00	8.50
SM2518A-4R7MHF	4.70	23.00	25.00	7.00	6.50
SM2518A-6R8MHF	6.80	36.00	41.00	6.50	5.50

3. Mechanical Dimensions of SM2518A series (unit: mm):



Pad Dimension	SM2518A
F	8.40 Typ.
G	3.70 Typ.
H	3.50 Typ.

Type	A	B	C	D	E
SM2518A	7.00 ± 0.30	6.60 ± 0.20	4.80 ± 0.20	3.00 ± 0.30	1.60 ± 0.30

● New York 1 914 347 2474 ● Taipei 886 2 2698 8669 ● Kaohsiung 886 7 350 2275
 ● Japan 81 568 85 2830 ● Shenzhen 86 755 8418 6263 ● Shanghai 86 21 5424 5141 ● Hong Kong 852 9688 9767
 ● sales@ITG-Electronics.com ● www.ITG-Electronics.com Revision A.1 : June 08, 2018

*Due to continuous product improvement, all specifications are subject to change without prior notice. Kindly contact an ITG field application engineer or a sales representative prior to purchase.







SM2518A Series



Notes:

1. Test conditions: 100KHz, 1.0V, 25°C ambient temperature .
2. Isat: DC current that causes inductance to drop 30%(Typ.) from OCL (Ta=25°C).
3. Irms: DC current for an approximate temperature rise of 40°C without core loss. Derating is necessary for AC currents. PCB pad layout, trace thickness and width, air-flow and proximity of other heat generating components will affect the temperature rise. It is recommended the part temperature not exceed 125° C under worst case operating conditions as verified in the end application.

4. Inductance vs. Current vs. Temperature Rise Characteristics of SM2518A Series :



● New York 1 914 347 2474 ● Taipei 886 2 2698 8669 ● Kaohsiung 886 7 350 2275
 ● Japan 81 568 85 2830 ● Shenzhen 86 755 8418 6263 ● Shanghai 86 21 5424 5141 ● Hong Kong 852 9688 9767
 ● sales@ITG-Electronics.com ● www.ITG-Electronics.com Revision A.1 : June 08, 2018







**Due to continuous product improvement, all specifications are subject to change without prior notice. Kindly contact an ITG field application engineer or a sales representative prior to purchase.*



SM2518A Series



4. Inductance vs. Current vs. Temperature Rise Characteristics of SM2518A Series :



● New York 1 914 347 2474 ● Taipei 886 2 2698 8669 ● Kaohsiung 886 7 350 2275
 ● Japan 81 568 85 2830 ● Shenzhen 86 755 8418 6263 ● Shanghai 86 21 5424 5141 ● Hong Kong 852 9688 9767
 ● sales@ITG-Electronics.com ● www.ITG-Electronics.com Revision A.1 : June 08, 2018

*Due to continuous product improvement, all specifications are subject to change without prior notice. Kindly contact an ITG field application engineer or a sales representative prior to purchase.




SM2518A Series



5. PACKAGE SPECIFICATION.(UNIT:mm):


(1).ENCAPSULATION MODE:




(2).DIMENSION(mm):

W	A0	B0	K0	P1	P0	P2	D0	D1	F	E1	T
16.0±0.30	7.0±0.10	7.3±0.10	5.40±0.10	12.0±0.10	4.0±0.10	2.0±0.10	1.5±0.10	1.5±0.10	7.5±0.10	1.75±0.10	0.40±0.05

(3).REEL SIZE:



(4).PACKAGE MODE:



(5).PACKAGING LIST:

No.	Packing Part	Dimension (mm)	Material	Quantity
1	Reel	330	Plastic	1000Pcs / Reel
2	Bag	450 X 360 X 0.075	Plastic	1Reel / Bag
3	Small Box	340 X 335 X 45	Paper	2Bag / Small Box
4	Middle Box	356 X 350 X 226	Paper	4Small Boxes / Middle Box
5	Outer Box	378 X 362 X 252	Paper	1Middle Box / Outer Box

(6).WEIGHT: N.W: 1.26 g/pcs (APPROX), TOTAL 10.08 Kg(APPROX),G.W:TOTAL 15.68Kg (APPROX).

(7).Storage conditions: -40°C~85°C ,75%RH (Max.).

● New York 1 914 347 2474 ● Taipei 886 2 2698 8669 ● Kaohsiung 886 7 350 2275
● Japan 81 568 85 2830 ● Shenzhen 86 755 8418 6263 ● Shanghai 86 21 5424 5141 ● Hong Kong 852 9688 9767
● sales@ITG-Electronics.com ● www.ITG-Electronics.com Revision A.1 : June 08, 2018

*Due to continuous product improvement, all specifications are subject to change without prior notice. Kindly contact an ITG field application engineer or a sales representative prior to purchase.



SM2518A Series



6.RELIABILITY TEST:

6.1 Mechanical Reliability		
Item	Specification and Requirement	Test Method
Solderability	The surface of terminal immersed shall be minimum of 95% covered with a new coating of solder	Solder heat proof: 1. Preheating: 160 ± 10 °C 2. Retention time: 245 ± 5 °C for 2 ± 0.5 seconds
Vibration	Inductance change: Within $\pm 10\%$ Without mechanical damage such as break	1. Vibration frequency: (10 Hz to 55 Hz to 10Hz) in 60 seconds as a period 2. Vibration time: Period cycled for 2 hours in each of 3 mutual perpendicular directions. 3. Amplitude: 1.5 mm max.
Shock	Inductance change: Within $\pm 10\%$ Without mechanical damage such as break	1. Peak value: 100 G 2. Duration of pulse: 11ms 3. 3 times in each positive and negative direction of 3 mutual perpendicular directions.
6.2 Endurance Reliability		
Thermal Shock	Inductance change: Within $\pm 10\%$ Without distinct damage in appearance	1. Repeat 100 cycles as follow: (-55 ± 2 °C; 30 ± 3 min) → (Room temp., 5 min) → (+155 ± 2 °C, 30 ± 3 min) → (Room temp., 5 min) 2. Recovery: 48 + 4 / -0 hours of recovery under the standard condition after the test.
High Temperature Resistance	Inductance change: Within $\pm 10\%$ Without distinct damage in appearance	1. Environment condition: 85 ± 2 °C Applied Current: Rated current 2. Duration: 1000 + 4 / -0 hours
Humidity Resistance	Inductance change: Within $\pm 10\%$ Without distinct damage in appearance	1. Environment condition: 60 ± 2 °C Humidity: 90–95% Applied Current: Rated current 2. Duration: 1000 + 4 / -0 hours
Low Temperature Store	Inductance change: Within $\pm 10\%$ Without distinct damage in appearance	Store temperature: -55 ± 2 °C, 1000 + 4 / -0 hours
High Temperature Store	Inductance change: Within $\pm 10\%$ Without distinct damage in appearance	Store temperature: +125 ± 2 °C, 1000 + 4 / -0 hours

● New York 1 914 347 2474 ● Taipei 886 2 2698 8669 ● Kaohsiung 886 7 350 2275
● Japan 81 568 85 2830 ● Shenzhen 86 755 8418 6263 ● Shanghai 86 21 5424 5141 ● Hong Kong 852 9688 9767
● sales@ITG-Electronics.com ● www.ITG-Electronics.com Revision A.1 : June 08, 2018

**Due to continuous product improvement, all specifications are subject to change without prior notice. Kindly contact an ITG field application engineer or a sales representative prior to purchase.*



SM2518A Series



Soldering Reflow Chart

Stage	Precaution	Recommended temperature profile
Reflow soldering	Temperature profile can be referenced after confirming of adhesion , temperature of resistance to soldering heat , component size , soldering etc. sufficient . Note: please refer to the latest IPC/JEDEC J-STD-020: "Moisture/Reflow Sensitivity Classification for Nonhermetic Solid State Surface Mount Devices"	The graph shows Temperature in °C on the y-axis (25, 125, 220, 250, 260) and time on the x-axis. The profile starts at 25°C, ramps up to 125°C (labeled 240s to 480s), then continues to ramp up to 220°C (labeled 150s to 210s). A shaded cyan area indicates a recommended temperature range during this ramp. At 220°C, it holds for 60s to 90s, then ramps up to a peak of 260°C (labeled 10S (MAX)). After the peak, it shows a 'Natural cooling' curve.

● New York 1 914 347 2474 ● Taipei 886 2 2698 8669 ● Kaohsiung 886 7 350 2275
 ● Japan 81 568 85 2830 ● Shenzhen 86 755 8418 6263 ● Shanghai 86 21 5424 5141 ● Hong Kong 852 9688 9767
 ● sales@ITG-Electronics.com ● www.ITG-Electronics.com Revision A.1 : June 08, 2018

**Due to continuous product improvement, all specifications are subject to change without prior notice. Kindly contact an ITG field application engineer or a sales representative prior to purchase.*