




SL41329 Series



1. Features:

- Ferrite based SMD Inductor with lower core loss.
- Inductance:150nH to 170nH . Custom values are welcomed.
- High current output chokes, upto 84 Amp with approx. 20% roll off.
- Low Profile 8.00mm Max. height .
- Foot Print 10.41 x 8.50 mm Max.
- Ideal for Buck Converter, VRM & High Density Board Design.
- Operating frequency up to 1 MHz application.
- Operating Temperature Range -55°C to + 130°C , RoHs & HF compliance .
- T & R Qtys: 450 pcs , 13" Reel .




2. Electrical Characteristic of SL41329 Series:

Part Number	Inductance (uH) ±10%	DCR (mΩ) ± 5.0%	Isat ¹ (A) @25°C	Isat ² (A) @75°C	Isat ³ (A) @100°C	Irms (A) @25°C
SL41329A-R15KHF	0.150	0.135	84.00	77.00	71.00	64.00
SL41329A-R17KHF	0.170	0.135	71.00	62.00	59.00	64.00

3. Mechanical Dimension(Unit:mm):

A	B	C	D	E	F	G
Max.	Max.	Max.	Max.	Nom.	Nom.	Nom.
8.50	10.30	8.00	10.41	5.10	2.25	2.50



Note:

- 1>.Open Circuit Inductance (OCL) test condition:100KHz,0.1Vrms,0Adc ,at 25 °C.
- 2>.Full Load Inductance (FLL) Test condition:100KHz,0.1Vrms ,Isat ;(Ta=25 °C).
- 3>.Isat¹,Isat² & Isat³ : DC current that will cause inductance to drops approximately by 20% ;
- 4>. Irms: DC current for an approximate temperature rise of 40°C without core loss,.Derating is necessary for AC currents. PCB pad layout,trace thickness and width,air-flow and proximity of other heat generating components will affect the temperature rise. It is recommended the part temperature not exceed 130°C under worst case operating conditions verified in the end application.
- 5>.The nominal DCR is measured from point "a" to point"b",as shown above on the mechanical drawing.

4. Inductance Characteristics (Inductance vs. Current):

